Uncoated Steel Data Sheet



September 2019 - This literature supersedes all previous issues

XLERPLATE® steel

Counterweight

General description

Steel plate supplied to a broad chemical analysis range with no guaranteed mechanical properties.

Typical uses

Counterweight

Warnings

This material has no guaranteed mechanical properties.


This material is NOT recommended for structural applications.

No test certification is available for this product.

This material is NOT supplied to a specific standard. Surface and cut edge quality is not guaranteed to any standard and may be variable.

Sections > 150 mm will have minimal rolling reduction and may have low strength and toughness.

This material has no guaranteed weldability or formability properties.



Australian and International Standards

ISO 9001:2015 Quality System certified

Normal / optional supply conditions

	Normal
Thickness Range	10mm – 250mm
Availability	By enquiry only
Edge Condition	Untrimmed (Mill Edge)*
Tolerances Width / Length	-20 / +50 mm
Tolerances Thickness	+/- 5 mm
Ultrasonic Inspection	Nil
Surface Inspection	Nil
Certification	Nil

Optional supply conditions may be subject to dimensional restrictions

Chemical composition

Element	Guaranteed Maximum %
Carbon	0.5
Silicon	0.7
Manganese	2.0
Phosphorus	0.05
Sulfur	0.05
Aluminium	0.10

Other elements may be present. Note these values are indicative only.

Fire hazard properties

Test & Evaluation Method	Result
Combustibility test for materials (AS 1530.1-1994 (R2016))	Not deemed combustible (steel substrate) #

[#] These test results relate only to the behaviour of the test specimens of the material under the particular conditions of the test and they are not intended to be the sole criterion for assessing the potential fire hazard of the material in use.



To ensure you have the most current information

1800 024 402

steeldirect@bluescopesteel.com
For more information contact Steel Direct



The information contained in this datasheet is provided by way of general information about this product only, and has not been prepared with your specific needs in mind. We recommend that you seek BlueScope's advice as to the suitability of this product for the purpose(s) for which you propose to use it. To contact BlueScope for advice about your proposed use of this product, please contact Steel Direct. XLERPLATE®, BlueScope and the BlueScope brand mark are registered trade marks of BlueScope Steel Limited. © 2019 BlueScope Steel Limited ABN 16 000 011 058. All rights reserved.