


METLOK CYCLONIC 680®

CONCEALED FIX ROOF SYSTEM



A Met-TECH™ GUIDE


NOVEMBER 2018



Metroll®

BETTER SERVICE • BETTER BUILDING SOLUTIONS

METLOK CYCLONIC 680[®]



Metlok Cyclonic 680[®] is a concealed fix roof system designed for long run roofing applications in Wind Regions C1 & C2. It can also be used for walling. Metlok Cyclonic 680[®] is manufactured in a continuous roll form method from 0.42mm and 0.48mm BMT COLORBOND[®] steel, and ZINCALUME[®] steel. Metlok Cyclonic 680[®] is suitable for use in commercial and industrial applications for roof pitches as low as 1° (1 in 50).

FEATURES & BENEFITS

- Concealed fix
- Ideal for long runs
- Low pitch
- Designed for thermal expansion and contraction
- Easy clip install

METLOK CYCLONIC 680[®] - ROOFING

BMT mm	Steel Base Mpa	Mass CB* kg/m ²	Mass Zinc kg/m ²	Min. Pitch**
0.42	G550	4.74	4.66	1° (1 in 50)
0.48	G550	5.37	5.23	1° (1 in 50)

METLOK CYCLONIC 680[®] - WALLING

0.42	G550	4.74	4.66
0.48	G550	5.37	5.29

*CB = Colorbond[®]

** Minimum Roof Pitch - Roof Run, Length & Rainfall Intensity must be considered

What is Met-TECH[™]?

Met-TECH[™] is Metroll's

Technical Resource Centre. It is the one stop shop for all of Metroll's product and technical information.

Perfect for builders, contractors and specifiers to source all the information they may require. You can find other Met-TECH[™] items on our website

www.metroll.com.au/resources

LOAD SPAN TABLE - MAXIMUM SPANS (MM)

WIND CATEGORY	0.42 BMT		0.48 BMT	
	END	INTERNAL	END	INTERNAL
C1	1000	1300	1100	1300
C2	900	1150	900	1200

Spans are based on James Cook University Townsville Test Report No: TS965

End and Internal Spans may be increased when using Screw Fixing only but require consultation with a Certified Engineer.

CLIPS & FASTENERS



METLOK CYCLONIC 680® CLIP

Metlok Cyclonic 680® can be installed by either concealed clip fixing or screw fixing.

CLIP FIXING

TO METAL PURLINS (G450, Z350 & G500, Z350)

No.14 x 10 x 25mm Metal Tekes
(1.2mm min. thickness)

TO TIMBER BATTENS (MGP10, MGP12)

M5.5 x 40mm Batten Zips

TO TIMBER BATTENS (HARDWOOD)

Type 17 No.14 x 10 x 25mm

SCREW FIXING

TO METAL

No.14 x 10 x 75mm Metal Tekes
CYCLONE HIGH GRIP ASSEMBLY
For Cappings & Flashings use a
20mm bonded washer

TO TIMBER

Type 17 No.14 x 10 x 75mm
CYCLONE HIGH GRIP ASSEMBLY
For Cappings & Flashings use a
20mm bonded washer

DRAINAGE & OVERFLOW

Max Roof Run (m) for Slopes & Rainfall Intensity

Rainfall Intensity mm/hr.	Metlok Cyclonic 680® Roof Slope					
	1 in 50 1°	1 in 30 2°	1 in 20 3°	1 in 12 5°	1 in 7.5 7.5°	1 in 6 10°
100	245	306	365	442	355	610
150	166	210	245	306	357	416
200	122	158	179	225	265	310
250	101	125	142	180	212	250
300	82	103	120	155	170	210
400	76	92	107	136	160	186

- Rainwater run-off and drainage capacity may place some limitations on the total length of a sheet run and must be considered during the design and construction phase of a project.
- The total length of roof sheeting; which shall include end laps, expansion joints or steps and draining the roof in one direction, shall be considered as a single roof run.
- Thermal expansion must also be considered.
- Maximum production and transport lengths may limit availability.

THERMAL EXPANSION

Change in temperature will cause all metals to expand and contract. There is minimal effect with steel roofing and walling, however care must be taken when long sheet runs and used and high temperature variations occur.

LENGTH

Metroll supplies Metlok Cyclonic 680® cut to order as required; depending on load limit regulations set by local transport authorities. Lengths for manufacture need to be site measurements and not taken off plans. Length tolerance for Metlok Cyclonic 680® is ± 0 -15mm.

To prevent damage when lifting long lengths, ensure sheets are lifted with the use of multiple lift point spreader bars.

CUTTING

Cut sheets with a method and in a location so that damage is avoided to sheets and other building products. Material should be cut on the ground and not above other materials. Remove all swarf and debris from the work and installation area. Sheets may be cut using a power saw with a steel cutting blade, a power nibbler or with tin snips. Avoid using abrasive discs as these can cause edge and coating damage.

CARE, HANDLING & STORAGE

Care should be taken at all times when handling sheets to preserve the quality of the finish. Keep packs dry, stored clear of the ground and protected from rain and moisture. Any sheets which become wet should be separated, wiped and placed in the open air to dry.

WALKING ON METLOK CYCLONIC 680®

When walking on Metlok Cyclonic 680® roof sheeting always wear flat rubber soled shoes and only walk over areas where purlins or batten supports are installed. Walk in either pan next to lapped edge ribs.

CLEAN UP

Prior to departing the work site remove all foreign debris, screws, rivets and especially any swarf created by drilling or cutting from the roof surface and/or inside gutters. Failure to do so may result in premature corrosion of the roof or gutters.

MATERIAL COMPATIBILITY

Never use lead flashings with Metlok Cyclonic 680® sheeting made from COLORBOND® and ZINCALUME® steels. Avoid drainage from copper roofs onto COLORBOND®, ZINCALUME® or galvanised steel roofing or rainwater products. Lead, copper, bare metal and some chemically treated timbers are not compatible with Metlok Cyclonic 680®.

MATERIAL SPECIFICATION & SCOPE

All roofing and walling should be specified on drawings as Metlok Cyclonic 680[®], manufactured by Metroll Pty Ltd and installed in accordance with the manufacturers recommendations. Base sheet steel is G550 / AZ150 with specified finish.

ADVERSE CONDITIONS

Localised environmental conditions can impact the corrosive nature of a site which may impact on material choice. Conditions that may impact on material choice include; direction of prevailing winds, rainfall intensity, duration of exposure, temperature, shelter and areas not washed by rainfall. Contact your local Metroll branch if you intend to use Metlok Cyclonic 680[®] within 1km of industrial, chemical, marine or corrosive environments.

MAINTENANCE

Exterior surfaces not washed by rainfall should be washed on a regular basis.

AVAILABILITY & DELIVERY

Metlok Cyclonic 680[®] is available from Metroll Cairns, Townsville, Mackay, Rockhampton & Bundaberg only. Contact your local Metroll branch for lead times, colours and availability.

Ensuring suitable arrangements are made to assist the unloading of Metroll trucks will help supply material in good order. When lifting long lengths by crane please ensure the load is evenly spread. Where a crane cannot be made available it is the customers responsibility to provide sufficient labour to assist the driver in unloading.

ALIGNMENT CHECK DURING INSTALL

From time to time check that sheets continue to be parallel with the first sheet. This is done by taking two measurements across the width of one fixed sheet. Approximately half way through the job, perform a similar check from the finishing line.

STOP ENDS & LIPS - PITCH BELOW 15°

Turn the pans at the top of the sheets up 90° using a turn-up tool to prevent wind driven water entry.

Turn the pans at the bottom of the sheets down 30° using a turn-down tool to prevent water running back along the underside of the sheet.

ROOF PITCH, FLASHINGS & END LAPS

For roofs with continuous sheets and no end laps the minimum roof pitch is 1° (1 in 50). This minimum pitch must be adhered to and all points of the roof to prevent ponding. For roofs with end laps the minimum lap is 200mm for pitches between 5° and 15°, and 150mm above 15°. Allow a minimum of 50mm for projection into gutters.

Flashings must be of a compatible material and 150mm minimum cover.

For walls allow maximum end laps of 100mm. End laps in roofs of less than 5° should be sealed with a suitable sealant. The sealant should be applied in two runs; one at the low end of the lap to prevent moisture being drawn in by capillary action, the other should be at the high end of the lap to prevent condensation that may form under the top sheet from draining down the underside and entering the lap.

QLD

Cairns	07 4054 0888
Townsville	07 4779 8266
Mackay	07 4968 1255
Rockhampton	07 4920 0900
Bundaberg	07 4155 5999
Toowoomba	07 4634 6144
Sunshine Coast	07 5493 7872
Brisbane	07 3375 0100

NSW

Lismore	02 6622 6677
Tamworth	02 6765 4799
Newcastle	02 4954 5799
Sydney	1300 766 346
Dubbo	02 6883 4800
Wagga Wagga	02 5924 4500
Canberra	02 6298 2777

VIC

Preston	03 9480 3744
Laverton	03 8369 8300
Geelong	03 5248 2006
Ballarat	03 5335 6416
Pakenham	03 8710 9300
NT	
Darwin	08 8935 9555

TAS

Launceston	03 6335 8555
------------	--------------

SA

Adelaide	08 8282 3300
----------	--------------

WA

Perth	08 9365 5444
Bunbury	08 9796 9796
Albany	08 9841 6966

26 Metroll Branches Nationwide

visit our new website

metroll.com.au



Metroll Pty Ltd. ABN 97 001 446 439. All reasonable care has been taken in the compilation of the information contained in this brochure. All recommendations on the use of Metroll products are made without guarantee as conditions of use are beyond the control of Metroll Pty Ltd. It is the customers responsibility to ensure that the product is fit for its intended purpose and that the actual conditions of use are suitable. Metroll Pty Ltd. pursues a policy of continuous development and reserves the right to amend specifications without prior notice. The Metroll M and Logo are registered trademarks of Metroll Pty Ltd. COLORBOND[®], ZINCALUME[®], and GALVSPAN steels are all registered trademarks of BlueScope Steel Limited.

M680_NOV18