

METLOK[®] HP

DESIGN & INSTALLATION GUIDE

HIGH
PERFORMANCE
SPEEDIER
INSTALL

CONCEALED FIX ROOF SYSTEM



A Met-TECH[™] GUIDE

MAY 2026



Metroll[®]

BETTER SERVICE • BETTER BUILDING SOLUTIONS

METLOK® HP



Cover: 695mm Height: 40mm

FEATURES & BENEFITS

- Optimised underclip for speedy installation
- Concealed fix
- Ideal for long runs
- Low pitch

Metlok® HP (High Performance) is a concealed fix roof system designed for long run roofing applications. It can also be used for walling.

Whilst similar to Metlok 700®, Metlok® HP features an underclip, not an overclip. The Metlok® HP underclip does not require installation over the top of the sheets which allows for bulk clip installation to the purlins. This makes Metlok® HP installation speedier and easier.

Metlok® HP is manufactured in a continuous roll method from 0.42mm and 0.48mm BMT COLORBOND® and ZINCALUME® steels. Metlok® HP is suitable for use in commercial and industrial applications for roof pitches as low as 1 degree (1 in 50).

METLOK® HP - ROOFING

BMT mm	Steel Base Mpa	Mass CB* kg/m ²	Mass Zinc kg/m ²	Min. Pitch°	Max Spans mm**	
					End	Internal
0.42	G550	4.68	4.61	1° (1 in 50)	1800	2200
0.48	G550	5.32	5.24	1° (1 in 50)	2200	2800

METLOK® HP - WALLING

0.42	G550	4.68	4.61	2050	2600
0.48	G550	5.32	5.24	2450	3000

*CB = Colorbond®

** Max. Spans are based on N2 Wind Category and 1.5mm substrate

CLIPS & FASTENERS FOR ROOFING & WALLING

Metlok® HP sheeting is fixed to supports by Metlok® HP Dekclips. Always face side laps away from the prevailing weather. Screws are available in a variety of materials, finishes and colours to match COLORBOND® pre-painted steel and design. Additional information on fastener finishes is in the BSL technical bulletin TB-16, which provides further guidance as to corrosivity category and fastener selection.

TIMBER SUPPORTS - HARD OR SOFT

#12 Hex Head Type 17 x 25mm. Add 10mm for softwood.

STEEL SUPPORTS 0.48 to 1.5mm BMT

M6 x 25mm Hex Head Universal Screw

STEEL SUPPORTS 1.5mm to 4.5mm BMT

#12 x 25mm Hex Head Self Drilling Screw

NOTE:

These fasteners do not make allowance for insulation blanket. Self drilling and tapping screws must comply with AS 3566.1

METLOK® HP DEKCLIP



What is Met-TECH™?

Met-TECH™ is Metroll's

Technical Resource Centre. It is the one stop shop for all of Metroll's product and technical information.

Perfect for builders, contractors and specifiers to source all the information they may require. You can find other Met-TECH™ items on our website

www.metroll.com.au/resources

SPRING CURVING

BMT mm	CONCAVE		CONVEX		
	Min. Radius	Max. Support Spacing	Min. Radius	Max. Support Spacing	Max. Radius for Drainage
0.42	90m	1200mm	90m	1200mm	220m
0.48	70m	1200mm	70m	1200mm	220m

DRAINAGE & OVERFLOW

Maximum Roof Run (m) for Slopes & Rainfall Intensity

Rainfall Intensity mm/hr	Metlok® HP Roof Slope					
	1 in 50 1°	1 in 30 2°	1 in 20 3°	1 in 12 5°	1 in 7.5 7.5°	1 in 6 10°
100	316	398	462	567	676	769
150	211	265	308	378	450	513
200	158	199	231	284	338	385
250	127	159	185	227	270	308
300	105	133	154	189	225	256
400	79	99	116	142	169	192

- Rainwater run-off and drainage capacity may place some limitations on the total length of a sheet run and must be considered during the design and construction phase of a project.
- The total length of roof sheeting; which shall include end laps, expansion joints or steps and draining the roof in one direction, shall be considered as a single roof run.
- Thermal expansion must also be considered.
- Maximum production and transport lengths may limit availability.

LENGTH

Metroll supplies Metlok® HP cut to order as required; depending on load limit regulations set by local transport authorities. Lengths for manufacture need to be site measurements and not taken off plans. Sheet length is obtained by measuring the distance from the ridges to the external edges or fascia and adding a minimum of 50mm for overhang into the gutter. To prevent damage when lifting long lengths, ensure sheets are lifted with the use of multiple lift point spreader bars.

CLEAN UP

Prior to departing the work site remove all foreign debris, screws, rivets and especially any swarf created by drilling or cutting from the roof surface and/or inside gutters. Failure to do so may result in premature corrosion.

CUTTING

Cut sheets with a method and in a location so that damage is avoided to sheets and other building products. Material should be cut on the ground and not above other materials. Remove all swarf and debris from the work and installation area. Sheets may be cut using a power saw with a steel cutting blade, a power nibbler or with tin snips. Avoid using abrasive discs as these can cause edge and coating damage.

MATERIAL COMPATIBILITY

Never use lead flashings with Metlok® HP sheeting made from COLORBOND® and ZINCALUME® steels. Avoid drainage from copper roofs onto COLORBOND®, ZINCALUME® or galvanised steel roofing or rainwater products. Lead, copper, bare metal and some chemically treated timbers are not compatible with Metlok® HP.

ADVERSE CONDITIONS


Localised environmental conditions can impact the corrosive nature of a site which may impact on material choice. Conditions that may impact on material choice include; direction of prevailing winds, rainfall intensity, duration of exposure, temperature, shelter and areas not washed by rainfall. Contact your local Metroll branch if you intend to use Metlok® HP within 1 km of industrial, chemical, marine or corrosive environments.

MATERIAL SPECIFICATION & SCOPE

All roofing and walling should be specified on drawings as Metlok® HP, manufactured by Metroll and installed in accordance with the manufacturers recommendations. Base sheet steel is G550 with specified finish.

AVAILABILITY & DELIVERY

Metlok® HP is available from Metroll VIC and select NSW branches. Contact your local Metroll branch for lead times, colours and availability. Ensuring suitable arrangements are made to assist the unloading of Metroll trucks will help supply material in good order. When lifting long lengths by crane please ensure the load is evenly spread. Where a crane cannot be made available it is the customers responsibility to provide sufficient labour to assist the driver in unloading.



**LOKSEAL™
FOR METLOK® HP**

LOKSEAL™ for Metlok® HP is a patented roof lap joining and sealing system for Metlok® HP roofing. It provides roofing installers with a fast, easy and cost effective solution to long-length roof sheet spans.

Visit metroll.com.au for more information.

METLOK® HP FOOT TRAFFIC

BMT (mm)	Internal Span (mm)	End Span (mm)
0.42	2200	1800
0.48	2800	2200

NOTE

- Foot traffic limits are based on AS/NZS 1170.1 for R2 - Other roofs.
- All traffic must use the designated foot traffic paths and, at all times, follow safe practices.

WALKING ON METLOK® HP

When walking on Metlok® HP roof sheeting always wear flat rubber soled shoes and only walk in sheet pans or near supports. In some applications, such as carports or verandahs, the use of crawl boards are recommended to avoid damage during installation

METLOK® HP OVERHANGS

The overhangs on Metlok® HP are limited to the values in the following table. Overhangs have a minimum length of 50mm. Stiffened overhangs incorporate an angle or gutter attached to the sheet end.

ROOFING		
BMT (mm)	Plain (mm)	Stiffened (mm)
0.42	250	500
0.48	300	600

WALLING		
BMT (mm)	Plain (mm)	Stiffened (mm)
0.42	300	500
0.48	350	600

- Plain overhangs are limited to 20% of the adjacent end span.
- Stiffened overhangs are limited to 33% of the adjacent end span.

TOLERANCES

Consideration should be given to the following manufacturing tolerances:

Length +0mm or -15mm **Width** +4mm or -4mm

THERMAL EXPANSION

Change in temperature will cause all metals to expand and contract. There is minimal effect with steel roofing and walling, however care must be taken when long sheet runs are used and high temperature variations occur.

MAINTENANCE

Exterior surfaces not washed by rainfall should be washed on a regular basis.

CYCLONIC AREAS

The information contained in this publication is suitable for non-cyclonic areas only.

CARE, HANDLING & STORAGE

Care should be taken at all times when handling sheets to preserve the quality of the finish. Keep packs dry, stored clear of the ground and protected from rain and moisture. Any sheets which become wet should be separated, wiped and placed in the open air to dry.

STOP ENDS & LIPS - PITCH BELOW 15°

Turn the pans at the top of the sheets up 90° using a turn-up tool to prevent wind driven water entry. Turn the pans at the bottom of the sheets down 30° using a turn-down tool to prevent water running back along the underside of the sheet.

ROOF PITCH & FLASHINGS

For roofs with continuous sheets and the minimum roof pitch is 1° (1 in 50). This minimum pitch must be adhered to and all points of the roof to prevent ponding. Allow a minimum of 50mm for projection into gutters. Flashings must be of a compatible material and 150mm minimum cover.

OIL CANNING

Oil canning appears as waviness or rippling in the flat areas of metal panels. It is a characteristic of light gauge cold rolled metal roofing and cladding products. It can occur on all types of metal sheeting and is not considered a defect. Oil canning is a cosmetic issue and does not affect the structural integrity of the product. Oil canning may occur due to installation methods, thermal expansion and contraction and material colour. To minimise the risk of oil canning, when handling the product avoid twisting or bending the sheets. For more information please refer to the Oil Canning Data Sheet on our website.

REFERENCED AUSTRALIAN STANDARDS

AS/NZS 1170.2	SAA Loading Codes - Wind Loads
AS 1397	Sheet & Strip Hot-Dipped Zinc Coated or Aluminium/Zinc Coated
AS 1526	One Part Polysulphide-based Sealing Compounds for the Building Industry
AS 1562.1	Design & Installation of Sheet & Wall Cladding, Part 1: Metal
AS/NZS 2179	Specifications for Rainwater Goods, Accessories & Fasteners - Metal Shape or Sheet Rainwater Goods and Metal Accessories and Fasteners
AS/NZS 2728	Prefinished/Prepainted Sheet Metal Products for Interior/Exterior Building Applications - Performance Requirements
AS 3566	Self-drilling Screws for the Building & Construction Industries

0.42mm & 0.48mm METLOK® HP LIMIT STATE CAPACITY TABLES

Tables and values must be used in conjunction with the Design Notes to Limit State Capacity Tables.
Tables based on product testing on the James Cook University Airbox.

0.42mm METLOK® HP WITH 3 FASTENERS/SHEET/BATTEN

LIMIT STATE	SPAN TYPE	SUPPORT THICKNESS (mm)	PRESSURE (kPa) FOR SPAN (mm)							
			900	1200	1500	1800	2100	2400	2700	3000
SERVICEABILITY	Internal	All	2.95	2.63	2.31	2.04	1.77	1.45	1.20	0.95
	End	All	2.91	2.58	2.36	1.98	1.55	1.15	0.75	0.38
STRENGTH	Internal	>1.50	2.79	2.58	2.36	2.23	2.10	1.75	1.12	0.75
		1.20	2.79	2.58	2.36	2.23	2.10	1.75	1.12	0.75
		1.00	2.79	2.58	2.36	2.23	2.10	1.75	1.12	0.75
		0.75	2.79	2.58	2.36	2.23	2.10	1.75	1.12	0.75
		0.55	2.79	2.58	2.14	1.79	1.53	1.34	1.12	0.75
		0.48	2.79	2.32	1.86	1.55	2.10	1.16	1.03	0.75
	End	>1.50	2.62	2.36	2.20	2.04	1.87	1.56	1.00	0.67
		1.20	2.62	2.36	2.20	2.04	1.87	1.56	1.00	0.67
		1.00	2.62	2.36	2.20	2.04	1.87	1.56	1.00	0.67
		0.75	2.62	2.36	2.20	2.04	1.87	1.56	1.00	0.67
		0.55	2.62	2.36	1.95	1.62	1.39	1.22	1.00	0.67
		0.48	2.62	2.11	1.69	1.41	1.21	1.06	0.94	0.67

0.48mm METLOK® HP WITH 3 FASTENERS/SHEET/BATTEN

LIMIT STATE	SPAN TYPE	SUPPORT THICKNESS (mm)	PRESSURE (kPa) FOR SPAN (mm)							
			900	1200	1500	1800	2100	2400	2700	3000
SERVICEABILITY	Internal	All	3.25	2.90	2.56	2.23	2.02	1.91	1.74	1.50
	End	All	3.25	2.86	2.36	1.95	1.67	1.35	1.28	1.15
STRENGTH	Internal	>1.50	4.45	4.06	3.66	3.37	3.07	2.72	2.51	2.30
		1.20	4.45	4.06	3.66	3.33	2.86	2.50	2.22	2.00
		1.00	4.45	4.06	3.66	3.10	2.65	2.32	2.06	1.86
		0.75	4.45	3.93	3.14	2.62	2.25	1.96	1.75	1.57
		0.55	3.57	2.68	2.14	1.79	1.53	1.34	2.51	2.30
		0.48	3.10	2.32	1.86	1.55	1.33	1.16	1.03	0.93
	End	>1.50	4.02	3.66	3.31	2.95	2.51	2.29	2.05	1.50
		1.20	4.02	3.66	3.31	2.95	2.51	2.27	2.02	1.50
		1.00	4.02	3.66	3.31	2.81	2.41	2.11	1.88	1.50
		0.75	4.02	3.57	2.86	2.38	2.04	1.79	1.59	1.43
		0.55	3.25	2.44	1.95	1.62	1.39	1.22	2.05	0.84
		0.48	2.81	2.11	1.69	1.41	1.21	1.06	0.94	0.84

DESIGN NOTES

- For timber battens/purlins, use >1.50 support thickness values.
- Type 17 screws must penetrate more than 25mm into hardwood or 35mm into softwood.
- Metal supports are produced from hi-tensile steel.
- For most economic results use longer internal spans than end spans (in a ratio of 10:8).
- Equal span systems must be designed using end span values.

0.42mm & 0.48mm METLOK® HP SPAN CHART

Tables and values must be used in conjunction with the Design Notes to Limit State Capacity Tables.
Tables based on product testing on the James Cook University Airbox.

0.42mm METLOK® HP

FASTENER FREQUENCY	SPAN TYPE	SUPPORT THICKNESS (mm)	ROOF SPANS (mm) FOR WIND CATEGORY						WALL SPANS (mm) FOR WIND CATEGORY					
			N1	N2	N3	N4	N5	N6	N1	N2	N3	N4	N5	N6
3+ clips per sheet	Internal	>1.50	2200	2200	1000				2800	2600	2150			
		1.20	2200	2200	1000				2800	2600	2150			
		1.00	2200	2200	1000				2800	2600	2150			
		0.75	2200	2200	1000				2800	2600	2150			
		0.55	2200	1950	1000				2800	2600	1650			
		0.48	2200	1700	1000				2800	2300	1450			
	End	>1.50	1800	1800	800				2200	2050	1700			
		1.20	1800	1800	800				2200	2050	1700			
		1.00	1800	1800	800				2200	2050	1700			
		0.75	1800	1800	800				2200	2050	1700			
		0.55	1800	1550	800				2200	2050	1350			
		0.48	1800	1350	800				2200	1800	1150			

0.48mm METLOK® HP

FASTENER FREQUENCY	SPAN TYPE	SUPPORT THICKNESS (mm)	ROOF SPANS (mm) FOR WIND CATEGORY						WALL SPANS (mm) FOR WIND CATEGORY					
			N1	N2	N3	N4	N5	N6	N1	N2	N3	N4	N5	N6
3+ clips per sheet	Internal	>1.50+	2800	2800	2400	1200			3000	3000	3000	2150	900	
		1.20	2800	2800	2200	1200			3000	3000	2950	1950	900	
		1.00	2800	2800	2050	1200			3000	3000	2700	1850	900	
		0.75	2800	2700	1700	1150			3000	3000	2300	1550	900	
		0.55	2700	1950	1250	850			3000	2600	1650	1100	750	
		0.48	2400	1700	1100	700			3000	2300	1450	950	650	
	End	>1.50	2200	2200	1900	950			2500	2450	2400	1700	700	
		1.20	2200	2200	1750	950			2500	2450	2350	1550	700	
		1.00	2200	2200	1650	950			2500	2450	2150	1450	700	
		0.75	2200	2150	1350	900			2500	2450	1850	1250	700	
		0.55	2150	1550	1000	650			2500	2100	1350	900	600	
		0.48	1900	1350	850	550			2500	1800	1150	750	500	

DESIGN NOTES

- Spans shown reflect the minimum value of the Serviceability, Strength and Foot Traffic tables.
- The Wind Category is based on AS 4055 and results include an allowance for local pressure factors.
- If roof pitch is less than 10 degrees, then increase the Wind Category upwards by 1, and apply to an area not less than 1.2m from all corners.
- For timber battens/purlins use >1.50 support thickness values.
- Metal supports are produced from hi-tensile steel.
- For most economic results use longer internal spans than end spans (in a ratio of 10:8).
- Equal span systems must be designed using end span values.

METLOK® HP INSTALLATION


BEFORE COMMENCING INSTALLATION

Ensure cladding support is in the same plane. Ensure sheet overhang does not exceed recommendations. Check roof pitch is within minimum recommendations. For maximum hold, check first and last supports and clips are at least 75mm from the end of the sheet. Ensure set out is correct to avoid complicated post-install rectification. Installation is quicker if all clips are installed before the sheeting.

SHEET PLACEMENT PRIOR TO INSTALL


Determine prevailing wind and weather direction for maximum weather tightness. Identify downward direction and start install from that end.

Turn sheets on the ground rather than on the roof, this is easier and safer. Before lifting ensure sheets are the correct way up and the overlapping side is facing the edge of the roof where installation will commence. Position sheet bundles over firm supports, not at mid span of roof members.




INSTALLATION STEPS

1. Install safety wire and insulation as per manufacturers recommendations.
2. Position the first Metlok clip by fixing to the support member nearest the roof edge.



3. Fix the clip as indicated. Ensure the clip is 90° to the edge of the sheet and facing the direction required for laying.


4. Using a string line align the clips using the first sheet as a straight edge. Fix a clip to each support member working towards the high end of the roof.



5. In accordance with the manufacturers recommendations, fix the Hex-head fasteners through the top of the clip into the support member.




6. Continue to work along the roof edge ensuring correct alignment at its ends relative to the gutter and ridge, (parapet or transverse wall).
7. After all of the initial first clips have been installed, attach the second clip row to each purlin. If desired, all clips can be attached to the purlins at this stage.
8. Measure the distance from the gutter end of the sheet to the support.
9. The first sheet must be placed square to adjacent edges. Position the first sheet so it overhangs the desired amount (normally 50mm) into the gutter.




10. The order in which the ribs are snapped into place is important. Start with Rib 2, then the adjacent Rib 3 and move to the next purlin and repeat.

- Once all second and third ribs have been snapped into place, secure the overlap by walking along the edge and gently engaging the overlap. Ensure the overlap is fully engaged for the entire sheet length before placing the next sheet.



- Continue to lay at least two rows of clips in advance of the laid sheets to all of the support members



- Position the next sheet taking care to ensure it positively engages the full length of the edge of the preceding sheet.
- Engage all clips and sheets as per Steps 10 - 13.
- If the final space is less than a full sheet width, the sheet can be cut and clips shortened as required.

ALIGNMENT CHECK DURING INSTALL

From time to time check that sheets continue to be parallel with the first sheet. This is done by taking two measurements across the width of one fixed sheet. Approximately half way through the job, perform a similar check from the finishing line.

INSTALLATION FOR WALL APPLICATIONS

The procedure for walls is similar to roof installation. Sheets can be prevented from sliding downwards by pierce fixing through each sheet beneath the flashing or canopy along the top of the sheets.

POTENTIAL DISTORTION

Metlok® HP is a concealed fix roofing profile that is secured by fixing clips attached to the building substrate. The roof sheet is snapped into place over the clips. In some instances slight bulging or distortion may be seen around the fixing clips caused by slight misalignment of the structure or sheet during installation. This poses no issue to the structural integrity of the cladding and will not affect the longevity of, or the warranty for the BlueScope Steel material. To reduce distortion, always follow the recommended installation procedure, use care and attention and do not force the material into place.

INSTALL OF COMPATIBLE TRANSLUCENT SHEETS

Translucent sheeting experiences greater thermal expansion. As a consequence cladding should be fixed using oversized holes and sealing washers. Refer to fastener manufacturer for detail. When translucent sheeting is used in conjunction with concealed fixed cladding, ensure the fasteners do not penetrate the steel cladding. Do not exceed maximum span/support distances specified by the translucent sheeting manufacturer.

Available from the below Metroll branches

NSW

Albury	02 6043 6800
Canberra	02 6298 2777
Dubbo	02 6883 4800
Newcastle	02 4954 5799
Sydney	1300 766 346
Tamworth	02 6765 4799
Wagga Wagga	02 5924 4500

VIC

Ballarat	03 5335 6416
Geelong	03 5248 2006
Laverton	03 8369 8300
Pakenham	03 8710 9300
Sunshine	03 9480 3744



All reasonable care has been taken in the compilation of the information contained in this brochure. All recommendations on the use of Metroll products are made without guarantee as conditions of use are beyond the control of Metroll. It is the customers responsibility to ensure that the product is fit for its intended purpose and that the actual conditions of use are suitable. Metroll pursues a policy of continuous development and reserves the right to amend specifications without prior notice. The Metroll M and Logo are registered trademarks of Metroll. COLORBOND®, ZINCALUME®, GALVSPAN® steels are all registered trademarks of BlueScope Steel Limited.