

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

**Product name** PRE-PAINTED STEEL STRIP AND SHEET

**Synonyms** EXTERIOR HOT WATER PREPAINTED STEEL (XHW) • EXTERIOR MANUFACTURED ARTICLES PREPAINTED STEEL (XMA) • GENERAL MANUFACTURED ARTICLES PREPAINTED STEEL (GMA) • INTERBOND™ PREPAINTED STEEL (ITB) • INTERIOR FURNITURE AND SHELVING PREPAINTED STEEL (IFS) • INTERLINER PREPAINTED STEEL (ITL) • LAB PANEL MATERIAL • SFP • SIGN WRITING PANEL PREPAINTED STEEL (SWP) • SUPERIOR GLOSS ARTICLES PREPAINTED STEEL (SGA) • URW PREPAINTED STEEL (URW)

### 1.2 Uses and uses advised against

**Uses** METAL FABRICATION • PACKAGING • SIGN WRITING

### 1.3 Details of the supplier of the product

**Supplier name** BLUESCOPE STEEL LIMITED (ABN 16 000 011 058)

**Address** Level 11, 120 Collins St, Melbourne, VIC, 3000, AUSTRALIA

**Telephone** 1800 800 789 (Australia Only)

**Email** [steeldirect@bluescopesteel.com](mailto:steeldirect@bluescopesteel.com)

**Website** <http://www.bluescopesteel.com.au>

### 1.4 Emergency telephone numbers

**Emergency** 02 4275 7522 (24h)

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

### 2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

### 2.3 Other hazards

Precautionary statement – Prevention

P260 Do not breathe dust/fume.

P280 Wear protective gloves/protective clothing/eye protection.

Precautionary statement – Response

P370 In case of fire and/or explosion do not breathe fumes.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
BASE METAL:			
STEEL, comprised of:	12597-69-2	-	100%
IRON	7439-89-6	231-096-4	97 to 99%
MANGANESE	7439-96-5	231-105-1	<2%

METALLIC COATING:

**PRODUCT NAME PRE-PAINTED STEEL STRIP AND SHEET**

ALUMINIUM ZINC MAGNESIUM COATING, comprised of:	-	-	100-170 g/m <sup>2</sup> total both sides
ALUMINIUM	7429-90-5	231-072-3	47 to 57%
MAGNESIUM	7439-95-4	231-104-6	1 to 3%
SILICON	7440-21-3	231-130-8	<2%
ZINC	7440-66-6	231-175-3	Remainder
or			
ZINC COATING, comprised of:	-	-	275-450 g/m <sup>2</sup> total both sides
ALUMINIUM	7429-90-5	231-072-3	<0.5%
ANTIMONY	7440-36-0	231-146-5	<0.2%
ZINC	7440-66-6	231-175-3	Remainder

CHEMICAL TREATMENT:			
HEXAVALENT CHROMIUM COMPOUNDS	Mixture	Mixture	Max 30 mg/m <sup>2</sup> per side
or			
FLUOROTITANIUM COMPLEX	-	-	<15 mg/m <sup>2</sup> of Ti per side

PAINTED FINISH:			
PRIMER, comprised of:	-	-	5-10 micron per side
STRONTIUM CHROMATE, LESS THAN 5% IN DRY FILM	7789-06-2	232-142-6	<20% of primer layer
or			
ANTICORROSIVE ADDITIVE	-	-	<25% of primer layer
TOP/BACKING COAT, comprised of:	-	-	-
VARIOUS PAINT SYSTEMS (POLYESTER, SILICONE MODIFIED POLYESTER AND ALKYD): NO HAZARDOUS SUBSTANCES	-	-	~5-30 micron per side

PRODUCTS PROTECTED WITH CORSTRIP® FILM ONLY:			
POLYETHYLENE FILM	-	-	45 or 80 +/- 5 micron

**Ingredient Notes** Steel strip with either a hot dipped zinc or aluminium/zinc/magnesium alloy coating and a painted surface.

Note 1: Carbon, silicon, aluminium, titanium, niobium and copper may be intentionally added to some steel products at a concentration of typically less than 0.1% each.

Note 2: Other elements may be unintentionally introduced from the recycled steel used in our processes, including trace amounts of copper, chromium, silicon, molybdenum, vanadium, tin and nickel (typically <0.1% each).

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

**Eye** It is unlikely that this product will enter the eye(s) in the supplied form. If steel splinters enter the eye, obtain medical attention immediately.

**Inhalation** It is unlikely that this product can be inhaled in the supplied form.

**Skin** It is unlikely that this product will cause irritation to the skin in the supplied form. Wash affected area thoroughly with soap and water.

**Ingestion** It is unlikely that this product can be ingested in the supplied form.

**First aid facilities** Eye wash facilities and normal washroom facilities should be available.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

### 5.2 Special hazards arising from the substance or mixture

Base metal is non-combustible. However, under fire conditions, material may decompose and/or burn. Some parts of the packaging are combustible. When burnt or overheated the product and packaging may release combustion products including carbon monoxide and metallic oxides.

### 5.3 Advice for firefighters

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes.

### 5.4 Hazchem code

None allocated.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Product should be picked up with suitable lifting equipment. Wear appropriate gloves to avoid cuts when handling.

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

### 6.3 Methods of cleaning up

If spilt, collect and reuse where possible.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Product is expected to be formed, fastened and cut. Product should not be welded or sanded. Product should be picked up with suitable lifting equipment. Wear appropriate gloves to avoid cuts when handling. Maintain high standards of personal hygiene i.e. washing hands prior to eating, drinking, smoking or using toilet facilities. Sanding or grinding to expose or remove the primer layer may release particles containing strontium chromate, therefore such actions should be avoided to prevent the creation of airborne dust.

### 7.2 Conditions for safe storage, including any incompatibilities

The material as supplied is not known to be hazardous to the environment. Product must be stored and secured to prevent movement during storage and transport. Store in a dry environment to prevent corrosion in storage. For more information on storing this product, refer to the document 'Guidelines for storage and handling of BlueScope products' available from BlueScope Steel sales offices and website.

### 7.3 Specific end uses

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

**Exposure standards** Any operation, which has the potential of generating particulates including dust or fume, requires a risk assessment to be undertaken. This may require the involvement of an experienced Occupational Hygienist.

No exposure standards have been established for this material, however, the TWA exposure standards for dust not otherwise specified is 10 mg/m<sup>3</sup>.

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Aluminium (metal dust)	SWA [AUS]	--	10	--	--
Chromium (VI) compounds (as Cr)	SWA [AUS]	--	0.05	--	--

## PRODUCT NAME PRE-PAINTED STEEL STRIP AND SHEET

### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Use with good general ventilation. No special ventilation is required for the product as supplied. For processing operations that generate dust or fumes, the use of engineering controls may be necessary to maintain air concentrations below the relevant Workplace Exposure Standards. Pre-painted steel should not be sanded, ground or otherwise abraded, in any operation that will penetrate the surface coating and create airborne dust. Penetrating or removing the primer layer by sanding or grinding may release dust particles containing strontium chromate.

Chromium (VI) is classified as a category 1A carcinogen (known to have carcinogenic potential for humans) according to Safe Work Australia.

Strontium chromate is classified as a category 1A carcinogen (known to have carcinogenic potential for humans) according to Safe Work Australia.

### PPE

<b>Eye / Face</b>	Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 Eye Protectors for Industrial Applications.
<b>Hands</b>	Appropriate gloves should be worn when handling strip or sheet steel, to avoid cuts from splinters, burrs, sharp edges, and contact with any surface treatments including oils if they are present. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
<b>Body</b>	Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended.
<b>Respiratory</b>	Not generally required. If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable filter should be used. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	THIN STEEL COIL OR SHEET IN VARIOUS COLOURS
<b>Odour</b>	NOT APPLICABLE
<b>Flammability</b>	NON FLAMMABLE
<b>Flash point</b>	NOT APPLICABLE
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	Base metal: 1500°C (Approximately)
<b>Evaporation rate</b>	NOT APPLICABLE
<b>pH</b>	NOT APPLICABLE
<b>Vapour density</b>	NOT APPLICABLE
<b>Relative density</b>	7.85
<b>Solubility (water)</b>	INSOLUBLE
<b>Vapour pressure</b>	NOT APPLICABLE
<b>Upper explosion limit</b>	NOT APPLICABLE
<b>Lower explosion limit</b>	NOT APPLICABLE
<b>Partition coefficient</b>	NOT APPLICABLE
<b>Autoignition temperature</b>	NOT APPLICABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT APPLICABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT APPLICABLE

---

## 10. STABILITY AND REACTIVITY

---

### 10.1 Reactivity

Refer to 'Hazardous Reactions' below.

## PRODUCT NAME PRE-PAINTED STEEL STRIP AND SHEET

### 10.2 Chemical stability

Stable under recommended conditions of storage and handling.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur. Contact of metallic substances with acids and alkalis liberates hydrogen gas.

### 10.4 Conditions to avoid

None expected, when used as intended.

### 10.5 Incompatible materials

Incompatible with acids (e.g. nitric acid) and alkalis (e.g. sodium hydroxide).

### 10.6 Hazardous decomposition products

When burnt or overheated the product and packaging may emit carbon monoxide, metallic oxides and other products of combustion.

---

## 11. TOXICOLOGICAL INFORMATION

---

### 11.1 Information on toxicological effects

**Acute toxicity** This product is expected to be of low toxicity. Based on available data, the classification criteria are not met. It is unlikely that this product can be ingested in the supplied form. It is unlikely that this product can be inhaled in the supplied form. Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

#### Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
IRON	30000 mg/kg (rat)	--	--
MANGANESE	9000 mg/kg (rat)	--	> 5.14 mg/L/4hrs (rat)
SILICON	3,160 mg/kg (rat)	> 5,000 mg/kg (rabbit)	--

**Skin** It is unlikely that this product will cause irritation to the skin in the supplied form.

**Eye** It is unlikely that this product will enter the eye(s) in the supplied form.

**Sensitisation** Not expected to be a skin or respiratory sensitiser.

**Mutagenicity** Not considered to be a mutagenic hazard.

**Carcinogenicity** Not considered to be a carcinogenic hazard.

**Reproductive** Not considered to be toxic to reproduction.

**STOT - single exposure** Not expected to cause toxicity to a specific target organ.

**STOT - repeated exposure** Not expected to cause toxicity to a specific target organ.

**Aspiration** Not expected to be an aspiration hazard.

---

## 12. ECOLOGICAL INFORMATION

---

### 12.1 Toxicity

No ecological data available for this material.

### 12.2 Persistence and degradability

Not available.

### 12.3 Bioaccumulative potential

Not available.

### 12.4 Mobility in soil

Not available.

### 12.5 Other adverse effects

Not available.

---

## 13. DISPOSAL CONSIDERATIONS

---

## PRODUCT NAME PRE-PAINTED STEEL STRIP AND SHEET

### 13.1 Waste treatment methods

<b>Waste disposal</b>	This product can be recycled. Please contact your relevant waste management provider to discuss requirements for recycling the packaging material. If not recycled, any disposal of waste product should be in accordance with local regulations.
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	None allocated.	None allocated.	None allocated.
<b>14.2 Proper Shipping Name</b>	None allocated.	None allocated.	None allocated.
<b>14.3 Transport hazard class</b>	None allocated.	None allocated.	None allocated.
<b>14.4 Packing Group</b>	None allocated.	None allocated.	None allocated.

### 14.5 Environmental hazards

Not a Marine Pollutant.

### 14.6 Special precautions for user

**Hazchem code** None allocated.

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Manufactured in accordance with Section 7/Appendix I, Paint or Tinters of the SUSMP.

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings** **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**  
All components are listed on AIIC, or are exempt.

**Regulatory information** Not classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

REGULATION (EC) No 1907/2006 (REACH) Article 7.1 - Not Applicable

REGULATION (EC) No 1907/2006 (REACH) Article 7.2 - Not Applicable

REGULATION (EC) No 1907/2006 (REACH) Article 33 – This product contains strontium chromate

## 16. OTHER INFORMATION

### Additional information

SDS reviewed: December 2023. Supercedes: August 2023.

CORSTRIP®, BlueScope and the BlueScope brand mark are registered trademarks of BlueScope Steel Limited.

#### DISCLAIMER:

This SDS summarises to BlueScope Steel Limited's (BSL) best knowledge at the date of issue, the health and safety hazards of the relevant materials. As BSL is not aware of and can't control the conditions under which the material may be used, each user is responsible for making their own assessment of the appropriateness of the material for their planned use and to implement appropriate controls.

**RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ):** Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (highly acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**PRODUCT NAME    PRE-PAINTED STEEL STRIP AND SHEET**

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**